



S.E.K.

SILVERTRONIC

SMOKEMAN

SUNFLAG. SUPER>



MULTIMETER - LEAD SETS





- 2 way LED testers black/red multimeter connector leads
- Male/female round terminal to banana plug.
- Male/female flat blade terminal to banana plua.
- Variable resistors with banana terminals.
- Needle / piercing probes.
- Alligator clips.

MULTIMETER LEAD SET

Essential test leads. Potentiometer | piercing probes | crocodile | flat terminals | signal tester and more.



POWERING EV DIAGNOSTICS

2 PRONG VOLTAGE TESTER

Safely test voltage up to 1000V AC / DC. Able to verify the absence of voltage even with discharged batteries.

- Conforms with EN 61243-3. CAT III 1000V/CAT IV 600V.
- LED indication range: 12V -1000V AC / DC.
- Rugged double insulated wire. ►
- Continuity / Diode test. ►



INSULATION TESTER & MULTIMETER

Professional multimeter with insulation test function.

- Conforms to EN61010 / CAT III (1000V)/ CAT IV (600V).
- Supplied with high voltage probes, thermocouple & wireless USB cable

1000V CAT III \$569 ET2144

True RMS / IP67 ► waterproof rating. Use standalone or link wirelessly to a PC.









Testing range: 100 — 2,000 CCA.

\$359

INSULATION TESTER

Specially designed to test insulation on high voltage cables. Essential test tool for EV / Hybrid vehicles.

- Conforms to EN61010 / CAT III (1000V)
- Measure AC/DC volts Low resistance b
- measurements Measure continuity

1000V CAT III \$289

ET2134







2 PCE

ET9397

hi.

\$69

22

✓ 1 器第51

S119

CE

ROTARY DIAL



92 PIECE

\$359

ET2031B

►



12V WITH PRINTER











BACK PROBES – BORESCOPES



CHOOSE THE RIGHT BORESCOPE:

		r		
	ET0914	ET0916	ET0918	ET0510
SCREEN			\checkmark	\checkmark
SCREEN SIZE			3.5″	3.2″
SCREEN RESOLUTION			320 x 240 px	320 x 240 px
SENSOR RESOLUTION	1280 x 720 px	1280 x 720 px	1280 x 720 px	640 x 480 px
CAMERA DIA	5.5 mm	6 mm	5.5 mm	5.5 mm
ARTICULATION		\checkmark		
SIDE CAMERA	\checkmark		\checkmark	
CABLE LENGTH	1.5 m	1 m	1 m	1 m
WIFI	\checkmark	\checkmark	\checkmark	A

WIFI 3.5" SCREEN (WIRED)

High resolution 5.5 mm dia camera. Wifi connectivity.

- ▶ 3.5" TFT LCD
- 320 x 240px display ► resolution
- 1280 x 720px sensor ► resolution
- Rechargeable battery Þ Mirror / hook
- /maanet attachments 1 m cable

length



ET0918

WIFI (ARTICULATED) Wifi allows for easy connection to phone / PC / scan tool. 360 degree articulation. Supports both iOS / Android. Narrow 6mm camera ► 1m gooseneck cable 6MM DIA 1280 x 720px resolution \$489 Rechargeable battery h ET0916

3.2" SCREEN (WIRED)

High resolution 5.5mm diameter camera for auto / industrial applications. Images can be saved / transferred to PC.

- 3.2" TFT LCD ►
- 320 x 240px display resolution
- 640 x 480px sensor resolution
- Rechargeable battery
- Mirror / hook / magnet attachments
- 1m cable length







AC/DC current & voltage, resistance. capacitance, frequency, duty cycle, temperature.

ET2506

600V CAT III \$189 ET2602



COMMERCIAL VEHICLES



ET1850A

b Requires optional hydraulic pump (eg ET1129B / eg ET1129B /
 c -6-1/4" bore, up to 15" deep.
 c -6-1/4" bore, up to 15" deep.
 b Wide application across CAT / Cummins / Mack / Volvo etc
 s 9995

ET1940A

ET1181F

ET3036A)



CANDO HD DIAGNOSTIC SOLUTIONS



at least 1 CanDo Tablet Scan Tool

before being installed on other

computers).

FOR FURTHER ENQUIRIES OR TO

ARRANGE YOUR FREE TRIAL CALL: 1300 137 753

THE ULTIMATE USA TRUCK / PICKUP **OE DATA RESOURCE!**

DIAGNOSTICS

6



- Automatic CAN High and CAN Low identification
- Automatic baud rate ► detection
- ▶ Voltage measurement below 20V - whether signal is a pulse or constant voltage
- ► Remote device - monitor signals remotely!



ET3048

87 87a 30

TYPE A RELAY TYPE B RELAY

Not suitable for Type A relays common to Holden vehicles

87

87a





Diagnose IR (Infra Red) / RF (Radio Frequency) remote controls. Place remote control below the LCD screen. Press

will be displayed. 10Mhz – 1,000Mhz

9V battery included

DIAGNOSTICS – ELECTRICAL





POWER PROBE CIRCUIT TESTERS

\$79

ET3428



9

Geore Pla

\$829

ETPPMA

DIGITAL 6 - 48V DC CIRCUIT TESTERS

LED PROBE TESTER

- Spring cable extends to 3 m.
- Not for use with 240V AC.
- Not for use with airbags.

Real time voltage display, in addition to indicating power (RED) and ground (GREEN). Small testing current (<10 mA).

LED 4MM CONNECTOR KIT

A handy kit containing the ET3428, but with a 4mm connector - use with any standard multimeter probes.

Wire piercer / probes / alligator clip included.





POWER PROBE 3EZ

Perform battery checks, charging system checks, fuse checks, voltage checks, component tests... All at the flick of the switch, with guidance from our two new menu options: EZLEARNING and EZIDIAGNOSTIC.

- New larger LCD screen
- Upside down?
 No problem!
 New flip screen feature
- Menu driven. Makes navigating a breeze





- Transmitter quickly determines if circuit has an open or if circuit is short to ground.
- Works on both
 12V & 24V systems.

Makes locating shorts and opens quicker and more accurate than ever before.



OWER PROBE

►

POWER PROBE BASIC

Apply voltage from the Power Probe tip to quickly actuate components.



voltage, continuity or polarity. Green / red LEDs provide quick confirmation.

 6m heavy duty extension lead.



+BONUS

PPT5VA

	The Maestro – ETPPMA	PP4 — ETPP4	PP3 — ETPP3
Voltage Rating	12 - 24V DC	12 - 24V DC	12 - 24V DC
Display Type	Multi Line Colour	Multi Line Colour	1 Line LCD
Apply Power / Ground	\checkmark	\checkmark	\checkmark
Audio Tone	\checkmark	\checkmark	\checkmark
Voltage Drop Detection	\checkmark	\checkmark	\checkmark
Continuity Tester	\checkmark	\checkmark	\checkmark
Flashlight	\checkmark	\checkmark	\checkmark
Circuit Breaker	8A Thermal Self Resetting	8A Thermal Self Resetting	8A Thermal Manual Reset
DC Voltmeter	0.1 - 199.9V DC	0.1 - 199.9V DC	0.1 - 70.0V DC
DC Min / Max	Avg, Min, Max Simultaneously	Avg, Min, Max Simultaneously	Min / Max Mode Selectable
AC Voltmeter	0.1 - 199.9 VAC (RMS or P-P)	0.1 - 199.9 VAC (RMS or P-P)	0.1 - 70.0 VAC (P-P)
AC Min / Max	Avg, Min, Max Simultaneously	Avg, Min, Max Simultaneously	
Ohmmeter	0.1 - 10k Ohms	0.1 - 10k Ohms	
Frequency (Hz)	1 - 9999Hz / Duty %/PW	1 - 9999Hz / Duty %/PW	
Injector Test Mode	\checkmark	\checkmark	
Driver Test	\checkmark	\checkmark	
ECT Mode	\checkmark	\checkmark	
Display Waveforms	\checkmark		
Bluetooth	\checkmark		
Pro Series App	\checkmark		



Files can be emailed,

saved for future réference.

exported or simply

AIR BOY - SONSBEEK



PROFESSIONAL AIR TOOLS





SOCKETS – WHEEL NUT REMOVAL



Wheel nut sockets in common metric sizes. Plus new HALF SIZE sockets for chrome covers on nuts that have swollen. DON'T GET CAUGHT OUT!!!





17, 19, 21 17, 19, 21, 22 мм MM **4 PIECE 3 PIECE** \$79 \$99

ETR3





ENGINE





FLUID TRANSFER / TOOLBOX ORGANISERS



OIL - COOLANT



RECHARGEABLE TORCHES



WORKSHOP







YOUR ENDEAVOUR TOOLS DISTRIBUTOR:

<a href="mailto:

Stores advertised on this page of this catalogue are independent businesses. Every effort is made to ensure advertised stock is available, but due to factors beyond the control of Endeavour Tools Pty Ltd, products advertised in this catalogue may not be available at all stores. Pricing for products include GST are recommended only. Certain items may incur a freight charge in some stores. Endeavour Tools Pty Ltd reserves the right to correct printing errors and omissions. All sizes shown are approximate only, and accessories shown with the product are not included unless specified. All products in this catalogue were available at the time of preparation and Endeavour Tools will, within reason ensure stock of advertised product is available, but cannot be held responsible for unforseen shortfalls, beyond their control.



APEX[®]

ATP-Boxy

FOXWELL

∂GROZ

iroda